

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
9 January 2003 (09.01.2003)


PCT

(10) International Publication Number  
**WO 03/002416 A2**

- (51) International Patent Classification<sup>7</sup>: **B65D**
- (21) International Application Number: PCT/US02/20800
- (22) International Filing Date: 28 June 2002 (28.06.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/302,265 29 June 2001 (29.06.2001) US
- (71) Applicant: **THE PROCTER & GAMBLE COMPANY**  
[US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).
- (72) Inventors: **YELTON, Donald, William**; 2481 Kremer Lane, Villa Hills, KY 41017 (US). **FORES, Gary, Gerard**; 400 Glen Cove Avenue, Sea Cliff, NY 11579 (US).
- (54) **PEDICANO, Ernest, Accuco**; 11 Hertford Street, New Rochelle, NY 10801 (US).
- (74) Agents: **REED, T., David et al.**; The Procter & Gamble Company, 6110 Center Hill Drive, Cincinnati, OH 45224 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,

[Continued on next page]

(54) Title: DISPENSER FOR WIPES



(57) Abstract: A dispenser for wipes. The present dispenser comprises a unitary living hinge and a pop-up cover. The unitary hinge allows for simplicity of construction, processing, and use. It also eliminates the need for a secondary mechanical hinge. The pop-up cover permits easy one-handed wipe dispensing without requiring that the lid be manually held in an open position.

BEST AVAILABLE COPY

WO 03/002416 A2



GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declarations under Rule 4.17:**

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent

(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations

**Published:**

- without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

## DISPENSER FOR WIPES

### CROSS REFERENCE TO RELATED APPLICATION

5           This application claims the benefit of U.S. Provisional Application No. 60/302,265 filed June 29, 2001.

### FIELD OF THE INVENTION

          This invention relates to a dispenser for wipes which features a pop-up  
10   cover and pop-up wipes capability.

### BACKGROUND OF THE INVENTION

          One of the limitations of prior art wipe dispensers is that a single  
dispenser requires several different materials to construct the dispenser. For  
15   instance, the body of the dispenser may be made of one material, the lid of a  
second different material, and the hinge connecting the dispenser body to the  
lid of yet a third material. This adds complexity to the dispenser manufacturing  
process.

          Furthermore, the hinge is commonly comprised of some type of  
20   mechanical device such as a spring, a strap, or other like elastic material. Such  
devices are disclosed in EP 0952088 published on October 27, 1999 and in  
U.S. 5,699,912 issued to Ishikawa et al. on December 23, 1997. The drawback  
of these types of mechanical hinging devices is that they are subject to  
mechanical failure. Additionally, these types of mechanical hinging devices add  
25   further complexity to the dispenser manufacturing.

          Another common limitation of prior art wipes dispensers is that the wet  
wipe contained within the dispenser is not adequately protected from drying out  
when the lid is closed.

          The present invention overcomes these limitations. The dispenser  
30   comprises only two parts-- a body for containing the wipes and a lid that covers

the wipes dispensing aperture. There are no mechanical parts. A living hinge, which is part of the lid construction, is used for the purpose of opening and shutting the lid. Hence, the dispenser manufacturing process is greatly simplified. Additionally, the dispenser includes a sealing means for preventing  
5 evaporation of liquid from the wipes when the lid is in the closed position. Yet further, the lid is designed with a pop-up cover allowing for easy one-handed wipes dispensing without requiring the user to hold the cover in an open position while dispensing a wipe.

10

### SUMMARY OF THE INVENTION

The present invention relates to a dispenser for dispensing wipes. The dispenser comprises a lid which is attached to a body. The lid is constructed of a single unitary piece of material. The lid includes a dispensing aperture and a cover. The cover includes an exterior seal, an inner seal, a perimeter seal  
15 comprising a backside perimeter seal, and a locking mechanism. The lid also includes a hinge which connects the cover to the lid. The hinge includes a step, a hinge step contacting member, and a deflection member. The lid also includes an inner ring adjacent to the dispensing aperture. A middle ring is adjacent to the inner ring. An outer ring is adjacent to the middle ring. A lower  
20 lid is adjacent to the outer ring. The lower lid includes a depression member. The hinge step contacting member contacts the step creating a first interference resulting in the outward deflection of the deflection member and creating a first storage energy. The backside perimeter seal of the cover contacts the wall formed by the middle ring and the outer ring thereby creating a second  
25 interference resulting in additional storage energy. The exterior seal contacts the wall formed by the outer ring and the lid surface. The latch catch engages the locking mechanism.

The dispenser may have an inner ring which includes an outer tapered surface leading to the middle ring. The dispenser may also have an inner seal  
30 with a tapered surface. The dispenser may optionally include support ribs.

### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an isometric view of one embodiment of the dispenser of this invention.

Fig. 2 is a side view of the dispenser of Fig. 1 showing the cover in an open

5 position.

Fig. 2A is a cross-sectional view taken along line 4 - 4 of Fig. 2.

Fig. 2B is a cross-sectional view taken along line 4 - 4 of Fig. 2.

Fig. 2C is a cross-sectional view taken along line 4 - 4 of Fig. 2.

Fig. 3 is a side view of the dispenser of Fig. 1 showing the dispenser cover in a

10 closed position.

Fig. 3A is a cross-sectional view taken along line 6 - 6 of Fig. 3.

Fig. 4 is a partial top isometric view of the dispenser of Fig. 1.

Fig. 5 is a partial side isometric view of the dispenser of Fig. 1.

Fig. 6 is a partial top isometric view of the dispenser of Fig. 1 showing the cover

15 in a closed position.

Fig. 6A is a cross-sectional view taken along line 7 - 7 of Fig. 5.

### DETAILED DESCRIPTION OF THE INVENTION

This invention relates to a dispenser for dispensing wipes. Referring to  
20 Fig. 1, the dispenser 1 comprises a lid 3 which is attached to the body 5. The lid 3 comprises a dispensing aperture 64 and a cover 9 which is connected to the lid 3 by a hinge 51. The lid 3 and all its components are constructed from a single unitary piece of material. The lid 3 also includes an inner ring 66 adjacent to the dispensing aperture 64, a middle ring 68 adjacent to the inner  
25 ring 66, and an outer ring 70 adjacent to the middle ring 68. The inner ring 66 preferably has an outer tapered surface leading to the middle ring 68.

The lower lid 72 is adjacent to the outer ring 70. The lower lid 72 also includes a depression member 62. When the cover 9 is in a closed position such as shown in Fig. 6, the user may release the cover 9 into an open position  
30 such as shown in Figs. 1, 2, 4, and 5, by depressing the depression member 62. This then allows the cover 9 to pop-up.

Referring to Fig. 1, the cover 9 is comprised of a hinge 51. The hinge 51 includes a step 50 and a hinge step contacting member 52. The cover 9 also includes a perimeter seal 20 which comprises a backside perimeter seal 24. The cover 9 further includes an exterior seal 21 and an inner seal 22.  
5 Preferably the inner seal 22 has a tapered surface. The cover 9 also includes a locking mechanism 23. Optionally, the cover 9 may include one or more support ribs 45.

While not wishing to be limited by theory, it is believed that the pop-up feature of the cover 9 works by the following mechanism. Referring to Figs. 2,  
10 2A, 2B, and 2C, as a user begins to close cover 9 the hinge step contacting member 52 contacts the step 50. Referring to Fig. 2B, this creates a first interference 56 which results in the outward deflection of the deflection member 53. This first interference 56 creates a first storage energy. Referring to Fig. 2C, as the user continues to close the cover 9, a second interference 57 is  
15 created when the backside perimeter seal 24 of the cover 9 comes into contact with the wall 69 formed by the middle ring 68 and outer ring 70. This second interference 57 creates additional storage energy. As shown in Figs. 3A, 6, and 6A, the cover 9 is fully closed and sealed when the exterior seal 21 contacts the wall 71 formed by the outer ring 70 and lid surface 72 and the latch catch 61  
20 engages the locking mechanism 23. This creates a seal around the dispensing aperture 64 thereby preventing the loss of moisture from the wipes.

Optionally, one or more ribs 45 may be used as structural support for the cover 9 as shown in Fig. 1. As a user depresses the depression member 62, the storage energy is released thereby permitting the cover 9 to pop-up.

25 A suitable dispenser 1 for the present invention can be produced by injection molding or any other suitable technique familiar to those of ordinary skill in the art. A non-limiting suitable material of construction for the dispenser includes a plastic such as polypropylene. A suitable polypropylene includes a polypropylene having a melt flow rate of 1.9. One such polypropylene is sold as  
30 PP TR375 and commercially available from Equistar Chemicals LP of Houston, Texas.

While particular embodiments of the invention have been illustrated and described, it would be obvious to those skilled in the art that various changes and modifications can be made without departing from the scope and spirit of the invention.

## WHAT IS CLAIMED IS:

1. A dispenser for dispensing wipes said dispenser comprising,  
a lid which is attached to a body, said lid constructed of a single unitary piece of material said lid comprising:
  - a) a dispensing aperture;
  - b) a cover, said cover including an exterior seal, an inner seal, a perimeter seal comprising a backside perimeter seal, and a locking mechanism;
  - c) a hinge which connects said cover to said lid, said hinge including a step, a hinge step contacting member, and a deflection member,
  - d) an inner ring adjacent said dispensing aperture;
  - e) a middle ring adjacent said inner ring;
  - f) an outer ring adjacent said middle ring;
  - g) a lower lid adjacent to said outer ring, said lower lid including a depression member;whereby said hinge step contacting member contacts said step creating a first interference resulting in the outward deflection of said deflection member and creating a first storage energy, said backside perimeter seal of said cover contacting said wall formed by said middle ring and said outer ring thereby creating a second interference resulting in additional storage energy, said exterior seal contacting said wall formed by said outer ring and said lid surface, and said latch catch engages said locking mechanism.
2. The dispenser of Claim 1 wherein said inner ring has an outer tapered surface leading to said middle ring.
3. The dispenser of Claim 1 wherein said inner seal has a tapered surface.
4. The dispenser of Claim 1 wherein said dispenser is injection molded.
5. The dispenser of Claim 4 wherein said dispenser comprises polypropylene.



6. The dispenser of Claim 5 wherein said polypropylene has a melt flow rate of 1.9
7. The dispenser of Claim 1 further comprising support ribs.




Fig 2






Fig. 2A








Fig 3






Fig. 3A










Fig. 6





Fig. 6A



(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
9 January 2003 (09.01.2003)


PCT

(10) International Publication Number  
**WO 03/002416 A3**

- (51) International Patent Classification<sup>7</sup>: **B65D 83/08**, 43/16, A47K 10/42
- (21) International Application Number: PCT/US02/20800
- (22) International Filing Date: 28 June 2002 (28.06.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/302,265 29 June 2001 (29.06.2001) US
- (71) Applicant: **THE PROCTER & GAMBLE COMPANY** [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).
- (72) Inventors: **YELTON, Donald, William**; 2481 Kremer Lane, Villa Hills, KY 41017 (US). **FORES, Gary, Gerard**; 400 Glen Cove Avenue, Sea Cliff, NY 11579 (US). **PEDICANO, Ernest, Accuco**; 11 Hertford Street, New Rochelle, NY 10801 (US).
- (54) Agents: **REED, T., David et al.**; The Procter & Gamble Company, 6110 Center Hill Drive, Cincinnati, OH 45224 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: DISPENSER FOR WIPES



WO 03/002416 A3

(57) Abstract: A dispenser for wipes. The present dispenser comprises a unitary living hinge and a pop-up cover. The unitary hinge allows for simplicity of construction, processing, and use. It also eliminates the need for a secondary mechanical hinge. The pop-up cover permits easy one-handed wipe dispensing without requiring that the lid be manually held in an open position.

**Declarations under Rule 4.17:**

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations *AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW*, *ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW)*, *Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM)*, *European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR)*, *OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)*

- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations

**Published:**

- with international search report

**(88) Date of publication of the international search report:**  
3 April 2003

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 02/20800

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B65D 83/08, B65D 43/16, A47K 10/42

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B65D, A47K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI, EPODOC

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 20000604 U1 (FHW FEUCHT-HYGIENE-WERK GMBH), 27 April 2000 (27.04.00), figure 2 --	1-7
A	EP 0955247 A1 (NICE-PAK INTERNATIONAL LTD.), 10 November 1999 (10.11.99), figures 1-3 --	1-7
A	PATENT ABSTRACTS OF JAPAN 02 Augusti 2000 (2000-08-02) & JP 2000-211680 A (NAKAMURA KENJI NAKAMURA KOJI abstract --	1-7

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

## \* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

11 October 2002

Date of mailing of the international search report

12 12 2002

Name and mailing address of the International Searching Authority



European Patent Office, P.B. 5818 Patentlaan 2  
NL-2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

ANNA AHLANDER/E1s  
Telephone No.

## INTERNATIONAL SEARCH REPORT

Int. application No.  
PCT/US 02/20800

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3982659 A (RICHARD T. ROSS), 28 Sept 1976 (28.09.76), figures 1-3 --	1-7
A	US 5582294 A (KIKUO YAMADA), 10 December 1996 (10.12.96), figures 3,4 --	1-7
A	US 5699912 A (HIROKI ISHIKAWA ET AL), 23 December 1997 (23.12.97), figure 1 --	1-7
A	US 6152322 A (MICHAEL MARINO), 28 November 2000 (28.11.00), figures 1-4 --	1-7
A	WO 9819934 A1 (THE PROCTER & GAMBLE COMPANY), 14 May 1998 (14.05.98), figures 4,5 -- -----	1-7



**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

30/09/02

International application No.

PCT/US 02/20800

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
DE	20000604	U1	27/04/00	NONE		
EP	0955247	A1	10/11/99	GB	2337041 A,B	10/11/99
				GB	9809723 D	00/00/00
US	3982659	A	28/09/76	CA	1047453 A	30/01/79
US	5582294	A	10/12/96	AU	3399495 A	08/10/96
				JP	3180114 B	25/06/01
				JP	8318977 A	03/12/96
				US	5729955 A	24/03/98
				WO	9629265 A	26/09/96
				ZA	9601901 A	12/09/96
US	5699912	A	23/12/97	AU	709893 B	09/09/99
				AU	5596896 A	02/01/97
				CA	2178999 A	16/12/96
				CN	1064321 B	11/04/01
				CN	1151962 A	18/06/97
				DE	69608495 D,T	26/10/00
				EP	0748748 A,B	18/12/96
				JP	9058725 A	04/03/97
				KR	195599 B	15/06/99
				SG	45488 A	16/01/98
US	6152322	A	28/11/00	NONE		
WO	9819934	A1	14/05/98	AU	5248398 A	29/05/98
				ES	1035581 U,Y	16/05/97

CORRECTED VERSION

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
9 January 2003 (09.01.2003)

PCT

(10) International Publication Number  
**WO 03/002416 A3**

(51) International Patent Classification<sup>7</sup>: **B65D 83/08**,  
43/16, A47K 10/42

(74) Agents: **REED, T., David et al.**; The Procter & Gamble  
Company, 6110 Center Hill Drive, Cincinnati, OH 45224  
(US).

(21) International Application Number: **PCT/US02/20800**

(22) International Filing Date: 28 June 2002 (28.06.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/302,265 29 June 2001 (29.06.2001) US

(71) Applicant: **THE PROCTER & GAMBLE COMPANY**  
[US/US]; One Procter & Gamble Plaza, Cincinnati, OH  
45202 (US).


(72) Inventors: **YELTON, Donald, William**; 2481 Kremer  
Lane, Villa Hills, KY 41017 (US). **FORES, Gary, Ger-**  
**ard**; 400 Glen Cove Avenue, Sea Cliff, NY 11579 (US).  
**PEDICANO, Ernest, Accuco**; 11 Hertford Street, New  
Rochelle, NY 10801 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT (util-  
ity model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA,  
CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (util-  
ity model), DE, DK (utility model), DK, DM, DZ, EC, EE  
(utility model), EE, ES, FI (utility model), FI, GB, GD, GE,  
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ,  
LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,  
MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD,  
SE, SG, SI, SK (utility model), SK, SL, TJ, TM, TN, TR,  
TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,  
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent  
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,  
NE, SN, TD, TG).

[Continued on next page]

(54) Title: DISPENSER FOR WIPES



(57) Abstract: A dispenser for wipes. The present dispenser comprises a unitary living hinge and a pop-up cover. The unitary hinge allows for simplicity of construction, processing, and use. It also eliminates the need for a secondary mechanical hinge. The pop-up cover permits easy one-handed wipe dispensing without requiring that the lid be manually held in an open position.

WO 03/002416 A3

**Declarations under Rule 4.17:**

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)*
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations*

**Published:**

- *with international search report*

**(88) Date of publication of the international search report:**  
3 April 2003

**(48) Date of publication of this corrected version:**  
12 September 2003

**(15) Information about Correction:**  
see PCT Gazette No. 37/2003 of 12 September 2003, Section II

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## DISPENSER FOR WIPES

### CROSS REFERENCE TO RELATED APPLICATION

5        This application claims the benefit of U.S. Provisional Application No. 60/302,265 filed June 29, 2001.

### FIELD OF THE INVENTION

10       This invention relates to a dispenser for wipes which features a pop-up cover and pop-up wipes capability.

### BACKGROUND OF THE INVENTION

15       One of the limitations of prior art wipe dispensers is that a single dispenser requires several different materials to construct the dispenser. For instance, the body of the dispenser may be made of one material, the lid of a second different material, and the hinge connecting the dispenser body to the lid of yet a third material. This adds complexity to the dispenser manufacturing process.

20       Furthermore, the hinge is commonly comprised of some type of mechanical device such as a spring, a strap, or other like elastic material. Such devices are disclosed in EP 0952088 published on October 27, 1999 and in U.S. 5,699,912 issued to Ishikawa et al. on December 23, 1997. The drawback of these types of mechanical hinging devices is that they are subject to mechanical failure. Additionally, these types of mechanical hinging devices add  
25       further complexity to the dispenser manufacturing.

      Another common limitation of prior art wipes dispensers is that the wet wipe contained within the dispenser is not adequately protected from drying out when the lid is closed.

30       The present invention overcomes these limitations. The dispenser comprises only two parts-- a body for containing the wipes and a lid that covers

the wipes dispensing aperture. There are no mechanical parts. A living hinge, which is part of the lid construction, is used for the purpose of opening and shutting the lid. Hence, the dispenser manufacturing process is greatly simplified. Additionally, the dispenser includes a sealing means for preventing  
5 evaporation of liquid from the wipes when the lid is in the closed position. Yet further, the lid is designed with a pop-up cover allowing for easy one-handed wipes dispensing without requiring the user to hold the cover in an open position while dispensing a wipe.

## 10 SUMMARY OF THE INVENTION

The present invention relates to a dispenser for dispensing wipes. The dispenser comprises a lid which is attached to a body. The lid is constructed of a single unitary piece of material. The lid includes a dispensing aperture and a cover. The cover includes an exterior seal, an inner seal, a perimeter seal  
15 comprising a backside perimeter seal, and a locking mechanism. The lid also includes a hinge which connects the cover to the lid. The hinge includes a step, a hinge step contacting member, and a deflection member. The lid also includes an inner ring adjacent to the dispensing aperture. A middle ring is adjacent to the inner ring. An outer ring is adjacent to the middle ring. A lower  
20 lid is adjacent to the outer ring. The lower lid includes a depression member. The hinge step contacting member contacts the step creating a first interference resulting in the outward deflection of the deflection member and creating a first storage energy. The backside perimeter seal of the cover contacts the wall formed by the middle ring and the outer ring thereby creating a second  
25 interference resulting in additional storage energy. The exterior seal contacts the wall formed by the outer ring and the lid surface. The latch catch engages the locking mechanism.

The dispenser may have an inner ring which includes an outer tapered surface leading to the middle ring. The dispenser may also have an inner seal  
30 with a tapered surface. The dispenser may optionally include support ribs.

## BRIEF DESCRIPTION OF THE DRAWINGS

- Fig. 1 is an isometric view of one embodiment of the dispenser of this invention.  
Fig. 2 is a side view of the dispenser of Fig. 1 showing the cover in an open  
5 position.  
Fig. 2A is a cross-sectional view taken along line 4 - 4 of Fig. 2.  
Fig. 2B is a cross-sectional view taken along line 4 - 4 of Fig. 2.  
Fig. 2C is a cross-sectional view taken along line 4 - 4 of Fig. 2.  
Fig. 3 is a side view of the dispenser of Fig. 1 showing the dispenser cover in a  
10 closed position.  
Fig. 3A is a cross-sectional view taken along line 6 - 6 of Fig. 3.  
Fig. 4 is a partial top isometric view of the dispenser of Fig. 1.  
Fig. 5 is a partial side isometric view of the dispenser of Fig. 1.  
Fig. 6 is a partial top isometric view of the dispenser of Fig. 1 showing the cover  
15 in a closed position.  
Fig. 6A is a cross-sectional view taken along line 7 - 7 of Fig. 5.

## DETAILED DESCRIPTION OF THE INVENTION

This invention relates to a dispenser for dispensing wipes. Referring to  
20 Fig. 1, the dispenser 1 comprises a lid 3 which is attached to the body 5. The  
lid 3 comprises a dispensing aperture 64 and a cover 9 which is connected to  
the lid 3 by a hinge 51. The lid 3 and all its components are constructed from a  
single unitary piece of material. The lid 3 also includes an inner ring 66  
adjacent to the dispensing aperture 64, a middle ring 68 adjacent to the inner  
25 ring 66, and an outer ring 70 adjacent to the middle ring 68. The inner ring 66  
preferably has an outer tapered surface leading to the middle ring 68.

The lower lid 72 is adjacent to the outer ring 70. The lower lid 72 also  
includes a depression member 62. When the cover 9 is in a closed position  
such as shown in Fig. 6, the user may release the cover 9 into an open position  
30 such as shown in Figs. 1, 2, 4, and 5, by depressing the depression member  
62. This then allows the cover 9 to pop-up.

Referring to Fig. 1, the cover 9 is comprised of a hinge 51. The hinge 51 includes a step 50 and a hinge step contacting member 52. The cover 9 also includes a perimeter seal 20 which comprises a backside perimeter seal 24. The cover 9 further includes an exterior seal 21 and an inner seal 22.  
5 Preferably the inner seal 22 has a tapered surface. The cover 9 also includes a locking mechanism 23. Optionally, the cover 9 may include one or more support ribs 45.

While not wishing to be limited by theory, it is believed that the pop-up feature of the cover 9 works by the following mechanism. Referring to Figs. 2,  
10 2A, 2B, and 2C, as a user begins to close cover 9 the hinge step contacting member 52 contacts the step 50. Referring to Fig. 2B, this creates a first interference 56 which results in the outward deflection of the deflection member 53. This first interference 56 creates a first storage energy. Referring to Fig. 2C, as the user continues to close the cover 9, a second interference 57 is  
15 created when the backside perimeter seal 24 of the cover 9 comes into contact with the wall 69 formed by the middle ring 68 and outer ring 70. This second interference 57 creates additional storage energy. As shown in Figs. 3A, 6, and 6A, the cover 9 is fully closed and sealed when the exterior seal 21 contacts the wall 71 formed by the outer ring 70 and lid surface 72 and the latch catch 61  
20 engages the locking mechanism 23. This creates a seal around the dispensing aperture 64 thereby preventing the loss of moisture from the wipes.

Optionally, one or more ribs 45 may be used as structural support for the cover 9 as shown in Fig. 1. As a user depresses the depression member 62, the storage energy is released thereby permitting the cover 9 to pop-up.

25 A suitable dispenser 1 for the present invention can be produced by injection molding or any other suitable technique familiar to those of ordinary skill in the art. A non-limiting suitable material of construction for the dispenser includes a plastic such as polypropylene. A suitable polypropylene includes a polypropylene having a melt flow rate of 1.9. One such polypropylene is sold as  
30 PP TR375 and commercially available from Equistar Chemicals LP of Houston, Texas.

While particular embodiments of the invention have been illustrated and described, it would be obvious to those skilled in the art that various changes and modifications can be made without departing from the scope and spirit of the invention.



## WHAT IS CLAIMED IS:

1. A dispenser for dispensing wipes said dispenser comprising,  
a lid which is attached to a body, said lid constructed of a single unitary piece of material said lid comprising:
  - a) a dispensing aperture;
  - b) a cover, said cover including an exterior seal, an inner seal, a perimeter seal comprising a backside perimeter seal, and a locking mechanism;
  - c) a hinge which connects said cover to said lid, said hinge including a step, a hinge step contacting member, and a deflection member,
  - d) an inner ring adjacent said dispensing aperture;
  - e) a middle ring adjacent said inner ring;
  - f) an outer ring adjacent said middle ring;
  - g) a lower lid adjacent to said outer ring, said lower lid including a depression member;whereby said hinge step contacting member contacts said step creating a first interference resulting in the outward deflection of said deflection member and creating a first storage energy, said backside perimeter seal of said cover contacting said wall formed by said middle ring and said outer ring thereby creating a second interference resulting in additional storage energy, said exterior seal contacting said wall formed by said outer ring and said lid surface, and said latch catch engages said locking mechanism.
2. The dispenser of Claim 1 wherein said inner ring has an outer tapered surface leading to said middle ring.
3. The dispenser of Claim 1 wherein said inner seal has a tapered surface.
4. The dispenser of Claim 1 wherein said dispenser is injection molded.
5. The dispenser of Claim 4 wherein said dispenser comprises polypropylene.

6. The dispenser of Claim 5 wherein said polypropylene has a melt flow rate of 1.9
7. The dispenser of Claim 1 further comprising support ribs.

1/11




Fig. 1

2/11




Fig. 2

3/11




Fig. 2A

4/11




Fig. 2B

5/11




Fig. 2C

6/11




Fig. 3



7/11




Fig. 3A

8/11




Fig. 4



10/11




Fig. 6

11/11




Fig. 6A

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US 02/20800

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B65D 83/08, B65D 43/16, A47K 10/42  
According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B65D, A47K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI, EPODOC

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 20000604 U1 (FW FEUCHT-HYGIENE-WERK GMBH), 27 April 2000 (27.04.00), figure 2 --	1-7
A	EP 0955247 A1 (NICE-PAK INTERNATIONAL LTD.), 10 November 1999 (10.11.99), figures 1-3 --	1-7
A	PATENT ABSTRACTS OF JAPAN 02 Augusti 2000 (2000-08-02) & JP 2000-211680 A (NAKAMURA KENJI NAKAMURA KOJI abstract --	1-7

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

11 October 2002

Date of mailing of the international search report

12 12 2002

Name and mailing address of the International Searching Authority

European Patent Office, P.B. 5818 Patentlaan 2  
NL-2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

ANNA AHLANDER/E1s  
Telephone No.

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 02/20800

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3982659 A (RICHARD T. ROSS), 28 Sept 1976 (28.09.76), figures 1-3 --	1-7
A	US 5582294 A (KIKUO YAMADA), 10 December 1996 (10.12.96), figures 3,4 --	1-7
A	US 5699912 A (HIROKI ISHIKAWA ET AL), 23 December 1997 (23.12.97), figure 1 --	1-7
A	US 6152322 A (MICHAEL MARINO), 28 November 2000 (28.11.00), figures 1-4 --	1-7
A	WO 9819934 A1 (THE PROCTER & GAMBLE COMPANY), 14 May 1998 (14.05.98), figures 4,5 -- -----	1-7

# INTERNATIONAL SEARCH REPORT

Information on patent family members

30/09/02

International application No.  
PCT/US 02/20800

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
DE	20000604	U1	27/04/00	NONE		
EP	0955247	A1	10/11/99	GB	2337041 A,B	10/11/99
				GB	9809723 D	00/00/00
US	3982659	A	28/09/76	CA	1047453 A	30/01/79
US	5582294	A	10/12/96	AU	3399495 A	08/10/96
				JP	3180114 B	25/06/01
				JP	8318977 A	03/12/96
				US	5729955 A	24/03/98
				WO	9629265 A	26/09/96
				ZA	9601901 A	12/09/96
US	5699912	A	23/12/97	AU	709893 B	09/09/99
				AU	5596896 A	02/01/97
				CA	2178999 A	16/12/96
				CN	1064321 B	11/04/01
				CN	1151962 A	18/06/97
				DE	69608495 D,T	26/10/00
				EP	0748748 A,B	18/12/96
				JP	9058725 A	04/03/97
				KR	195599 B	15/06/99
				SG	45488 A	16/01/98
US	6152322	A	28/11/00	NONE		
WO	9819934	A1	14/05/98	AU	5248398 A	29/05/98
				ES	1035581 U,Y	16/05/97



CORRECTED VERSION

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
9 January 2003 (09.01.2003)


PCT

(10) International Publication Number  
**WO 03/002416 A3**

- (51) International Patent Classification<sup>7</sup>: **B65D 83/08**, 43/16, A47K 10/42
- (74) Agents: **REED, T., David et al.**; The Procter & Gamble Company, 6110 Center Hill Drive, Cincinnati, OH 45224 (US).
- (21) International Application Number: PCT/US02/20800
- (22) International Filing Date: 28 June 2002 (28.06.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/302,265 29 June 2001 (29.06.2001) US
- (71) Applicant: **THE PROCTER & GAMBLE COMPANY** [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).
- (72) Inventors: **YELTON, Donald, William**; 2481 Kremer Lane, Villa Hills, KY 41017 (US). **FORES, Gary, Gerard**; 400 Glen Cove Avenue, Sea Cliff, NY 11579 (US). **PEDICANO, Ernest, Accuco**; 11 Hertford Street, New Rochelle, NY 10801 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: DISPENSER FOR WIPES



(57) Abstract: A dispenser for wipes. The present dispenser comprises a unitary living hinge and a pop-up cover. The unitary hinge allows for simplicity of construction, processing, and use. It also eliminates the need for a secondary mechanical hinge. The pop-up cover permits easy one-handed wipe dispensing without requiring that the lid be manually held in an open position.

WO 03/002416 A3

**Declarations under Rule 4.17:**

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations

**Published:**

- with international search report

(88) Date of publication of the international search report:  
3 April 2003

(48) Date of publication of this corrected version:  
12 September 2003

(15) Information about Correction:  
see PCT Gazette No. 37/2003 of 12 September 2003, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

## DISPENSER FOR WIPES

### CROSS REFERENCE TO RELATED APPLICATION

5        This application claims the benefit of U.S. Provisional Application No. 60/302,265 filed June 29, 2001.

### FIELD OF THE INVENTION

10        This invention relates to a dispenser for wipes which features a pop-up cover and pop-up wipes capability.

### BACKGROUND OF THE INVENTION

15        One of the limitations of prior art wipe dispensers is that a single dispenser requires several different materials to construct the dispenser. For instance, the body of the dispenser may be made of one material, the lid of a second different material, and the hinge connecting the dispenser body to the lid of yet a third material. This adds complexity to the dispenser manufacturing process.

20        Furthermore, the hinge is commonly comprised of some type of mechanical device such as a spring, a strap, or other like elastic material. Such devices are disclosed in EP 0952088 published on October 27, 1999 and in U.S. 5,699,912 issued to Ishikawa et al. on December 23, 1997. The drawback of these types of mechanical hinging devices is that they are subject to mechanical failure. Additionally, these types of mechanical hinging devices add  
25        further complexity to the dispenser manufacturing.

      Another common limitation of prior art wipes dispensers is that the wet wipe contained within the dispenser is not adequately protected from drying out when the lid is closed.

30        The present invention overcomes these limitations. The dispenser comprises only two parts-- a body for containing the wipes and a lid that covers

the wipes dispensing aperture. There are no mechanical parts. A living hinge, which is part of the lid construction, is used for the purpose of opening and shutting the lid. Hence, the dispenser manufacturing process is greatly simplified. Additionally, the dispenser includes a sealing means for preventing  
5 evaporation of liquid from the wipes when the lid is in the closed position. Yet further, the lid is designed with a pop-up cover allowing for easy one-handed wipes dispensing without requiring the user to hold the cover in an open position while dispensing a wipe.

10

#### SUMMARY OF THE INVENTION

The present invention relates to a dispenser for dispensing wipes. The dispenser comprises a lid which is attached to a body. The lid is constructed of a single unitary piece of material. The lid includes a dispensing aperture and a cover. The cover includes an exterior seal, an inner seal, a perimeter seal  
15 comprising a backside perimeter seal, and a locking mechanism. The lid also includes a hinge which connects the cover to the lid. The hinge includes a step, a hinge step contacting member, and a deflection member. The lid also includes an inner ring adjacent to the dispensing aperture. A middle ring is adjacent to the inner ring. An outer ring is adjacent to the middle ring. A lower  
20 lid is adjacent to the outer ring. The lower lid includes a depression member. The hinge step contacting member contacts the step creating a first interference resulting in the outward deflection of the deflection member and creating a first storage energy. The backside perimeter seal of the cover contacts the wall formed by the middle ring and the outer ring thereby creating a second  
25 interference resulting in additional storage energy. The exterior seal contacts the wall formed by the outer ring and the lid surface. The latch catch engages the locking mechanism.

The dispenser may have an inner ring which includes an outer tapered surface leading to the middle ring. The dispenser may also have an inner seal  
30 with a tapered surface. The dispenser may optionally include support ribs.

### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an isometric view of one embodiment of the dispenser of this invention.  
Fig. 2 is a side view of the dispenser of Fig. 1 showing the cover in an open  
5 position.  
Fig. 2A is a cross-sectional view taken along line 4 - 4 of Fig. 2.  
Fig. 2B is a cross-sectional view taken along line 4 - 4 of Fig. 2.  
Fig. 2C is a cross-sectional view taken along line 4 - 4 of Fig. 2.  
Fig. 3 is a side view of the dispenser of Fig. 1 showing the dispenser cover in a  
10 closed position.  
Fig. 3A is a cross-sectional view taken along line 6 - 6 of Fig. 3.  
Fig. 4 is a partial top isometric view of the dispenser of Fig. 1.  
Fig. 5 is a partial side isometric view of the dispenser of Fig. 1.  
Fig. 6 is a partial top isometric view of the dispenser of Fig. 1 showing the cover  
15 in a closed position.  
Fig. 6A is a cross-sectional view taken along line 7 - 7 of Fig. 5.

### DETAILED DESCRIPTION OF THE INVENTION

This invention relates to a dispenser for dispensing wipes. Referring to  
20 Fig. 1, the dispenser 1 comprises a lid 3 which is attached to the body 5. The  
lid 3 comprises a dispensing aperture 64 and a cover 9 which is connected to  
the lid 3 by a hinge 51. The lid 3 and all its components are constructed from a  
single unitary piece of material. The lid 3 also includes an inner ring 66  
adjacent to the dispensing aperture 64, a middle ring 68 adjacent to the inner  
25 ring 66, and an outer ring 70 adjacent to the middle ring 68. The inner ring 66  
preferably has an outer tapered surface leading to the middle ring 68.

The lower lid 72 is adjacent to the outer ring 70. The lower lid 72 also  
includes a depression member 62. When the cover 9 is in a closed position  
such as shown in Fig. 6, the user may release the cover 9 into an open position  
30 such as shown in Figs. 1, 2, 4, and 5, by depressing the depression member  
62. This then allows the cover 9 to pop-up.

Referring to Fig. 1, the cover 9 is comprised of a hinge 51. The hinge 51 includes a step 50 and a hinge step contacting member 52. The cover 9 also includes a perimeter seal 20 which comprises a backside perimeter seal 24. The cover 9 further includes an exterior seal 21 and an inner seal 22. Preferably the inner seal 22 has a tapered surface. The cover 9 also includes a locking mechanism 23. Optionally, the cover 9 may include one or more support ribs 45.

While not wishing to be limited by theory, it is believed that the pop-up feature of the cover 9 works by the following mechanism. Referring to Figs. 2, 2A, 2B, and 2C, as a user begins to close cover 9 the hinge step contacting member 52 contacts the step 50. Referring to Fig. 2B, this creates a first interference 56 which results in the outward deflection of the deflection member 53. This first interference 56 creates a first storage energy. Referring to Fig. 2C, as the user continues to close the cover 9, a second interference 57 is created when the backside perimeter seal 24 of the cover 9 comes into contact with the wall 69 formed by the middle ring 68 and outer ring 70. This second interference 57 creates additional storage energy. As shown in Figs. 3A, 6, and 6A, the cover 9 is fully closed and sealed when the exterior seal 21 contacts the wall 71 formed by the outer ring 70 and lid surface 72 and the latch catch 61 engages the locking mechanism 23. This creates a seal around the dispensing aperture 64 thereby preventing the loss of moisture from the wipes.

Optionally, one or more ribs 45 may be used as structural support for the cover 9 as shown in Fig. 1. As a user depresses the depression member 62, the storage energy is released thereby permitting the cover 9 to pop-up.

A suitable dispenser 1 for the present invention can be produced by injection molding or any other suitable technique familiar to those of ordinary skill in the art. A non-limiting suitable material of construction for the dispenser includes a plastic such as polypropylene. A suitable polypropylene includes a polypropylene having a melt flow rate of 1.9. One such polypropylene is sold as PP TR375 and commercially available from Equistar Chemicals LP of Houston, Texas.

While particular embodiments of the invention have been illustrated and described, it would be obvious to those skilled in the art that various changes and modifications can be made without departing from the scope and spirit of the invention.

## WHAT IS CLAIMED IS:

1. A dispenser for dispensing wipes said dispenser comprising,  
a lid which is attached to a body, said lid constructed of a single unitary piece of material said lid comprising:
  - a) a dispensing aperture;
  - b) a cover, said cover including an exterior seal, an inner seal, a perimeter seal comprising a backside perimeter seal, and a locking mechanism;
  - c) a hinge which connects said cover to said lid, said hinge including a step, a hinge step contacting member, and a deflection member,
  - d) an inner ring adjacent said dispensing aperture;
  - e) a middle ring adjacent said inner ring;
  - f) an outer ring adjacent said middle ring;
  - g) a lower lid adjacent to said outer ring, said lower lid including a depression member;whereby said hinge step contacting member contacts said step creating a first interference resulting in the outward deflection of said deflection member and creating a first storage energy, said backside perimeter seal of said cover contacting said wall formed by said middle ring and said outer ring thereby creating a second interference resulting in additional storage energy, said exterior seal contacting said wall formed by said outer ring and said lid surface, and said latch catch engages said locking mechanism.
2. The dispenser of Claim 1 wherein said inner ring has an outer tapered surface leading to said middle ring.
3. The dispenser of Claim 1 wherein said inner seal has a tapered surface.
4. The dispenser of Claim 1 wherein said dispenser is injection molded.
5. The dispenser of Claim 4 wherein said dispenser comprises polypropylene.



6. The dispenser of Claim 5 wherein said polypropylene has a melt flow rate of 1.9

7. The dispenser of Claim 1 further comprising support ribs.

1/11




Fig. 1

2/11




Fig. 2

3/11




Fig. 2A

4/11




Fig. 2B

5/11




Fig. 2C

6/11




Fig. 3

7/11




Fig. 3A



8/11




Fig. 4

9/11




Fig. 5

10/11




Fig. 6

11/11




Fig. 6A

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 02/20800

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B65D 83/08, B65D 43/16, A47K 10/42

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B65D, A47K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI, EPODOC

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 20000604 U1 (FHW FEUCHT-HYGIENE-WERK GMBH), 27 April 2000 (27.04.00), figure 2 --	1-7
A	EP 0955247 A1 (NICE-PAK INTERNATIONAL LTD.), 10 November 1999 (10.11.99), figures 1-3 --	1-7
A	PATENT ABSTRACTS OF JAPAN 02 Augusti 2000 (2000-08-02) & JP 2000-211680 A (NAKAMURA KENJI NAKAMURA KOJI abstract --	1-7

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

\* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family


Date of the actual completion of the international search

11 October 2002

Date of mailing of the international search report

12.12.2002

Name and mailing address of the International Searching Authority



European Patent Office, P.B. 5818 Patentlaan 2  
NL-2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

ANNA AHLANDER/E1s  
Telephone No.

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 02/20800

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3982659 A (RICHARD T. ROSS), 28 Sept 1976 (28.09.76), figures 1-3 --	1-7
A	US 5582294 A (KIKUO YAMADA), 10 December 1996 (10.12.96), figures 3,4 --	1-7
A	US 5699912 A (HIROKI ISHIKAWA ET AL), 23 December 1997 (23.12.97), figure 1 --	1-7
A	US 6152322 A (MICHAEL MARINO), 28 November 2000 (28.11.00), figures 1-4 --	1-7
A	WO 9819934 A1 (THE PROCTER & GAMBLE COMPANY), 14 May 1998 (14.05.98), figures 4,5 -- -----	1-7

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

30/09/02

International application No.

PCT/US 02/20800

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
DE	20000604	U1	27/04/00	NONE		
EP	0955247	A1	10/11/99	GB	2337041 A,B	10/11/99
				GB	9809723 D	00/00/00
US	3982659	A	28/09/76	CA	1047453 A	30/01/79
US	5582294	A	10/12/96	AU	3399495 A	08/10/96
				JP	3180114 B	25/06/01
				JP	8318977 A	03/12/96
				US	5729955 A	24/03/98
				WO	9629265 A	26/09/96
				ZA	9601901 A	12/09/96
US	5699912	A	23/12/97	AU	709893 B	09/09/99
				AU	5596896 A	02/01/97
				CA	2178999 A	16/12/96
				CN	1064321 B	11/04/01
				CN	1151962 A	18/06/97
				DE	69608495 D,T	26/10/00
				EP	0748748 A,B	18/12/96
				JP	9058725 A	04/03/97
				KR	195599 B	15/06/99
				SG	45488 A	16/01/98
US	6152322	A	28/11/00	NONE		
WO	9819934	A1	14/05/98	AU	5248398 A	29/05/98
				ES	1035581 U,Y	16/05/97

**THIS PAGE BLANK (USPTO)**



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

$$\begin{array}{r} 37 \\ 2 \\ \hline 74 \end{array}$$